



Classification	<b>DX140 SLR</b>	<b>DX225 SLR</b>	<b>DX260 SLR</b>	<b>DX300 SLR</b>	<b>DX340 SLR</b>	<b>DX420 SLR</b>	<b>DX520 SLR</b>	<b>DX800 SLR</b>
Boom Length mm	7,000	8,500	9,300	10,000	10,500	10,700	11,000	11,000
Arm Length mm	5,000	6,200	6,800	7,000	7,500	7,600	8,000	8,000
Bucket Capacity mm	0.28	0.39	0.5	0.64	0.7	0.8	0.92	1.64
Shipping Length mm	10,120	12,317	14,350	14,370	15,310	15,250	16,090	15,805
Shipping Height mm	2,746	3,254	3,910	3,455	3,765	3,800	4,070	7,120
Shipping Width mm	2,590	2,990	3,200	3,200	3,280	3,350	3,340	3,560
Height over Cabin mm	2,773	2,975	2,970	3,065	3,125	3,154	3,350	3,530
C/Weight Clearance mm	894	1,055	1,110	1,150	1,195	1,265	1,460	1,540
House Width mm	2,540	2,710	2,710	2,960	2,990	2,990	2,990	3,410
Track Length mm	3,755	4,445	4,625	4,940	4,940	5,200	5,465	5,960
Working Ranges	<b>DX140 SLR</b>	<b>DX225 SLR</b>	<b>DX260 SLR</b>	<b>DX300 SLR</b>	<b>DX340 SLR</b>	<b>DX420 SLR</b>	<b>DX520 SLR</b>	<b>DX800 SLR</b>
Max. Digging Reach mm	12,150	15,380	16,500	17,520	18,550	19,000	19,610	20,100
Max. Digging Depth mm	9,840	11,660	12,500	13,875	14,510	14,800	15,130	14,450